


**SEMiX® 33c**

## Trench IGBT Modules

### SEMiX703GD126HDc

#### Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$  with positive temperature coefficient
- High short circuit capability
- UL recognised file no. E63532

#### Typical Applications\*

- AC inverter drives
- UPS
- Electronic Welding

#### Remarks

- Case temperatur limited to  $T_C=125^\circ\text{C}$  max.
- Not for new design


**GD**

Absolute Maximum Ratings					
Symbol	Conditions		Values	Unit	
<b>IGBT</b>					
$V_{CES}$			1200	V	
$I_C$	$T_j = 150^\circ\text{C}$	$T_c = 25^\circ\text{C}$	642	A	
		$T_c = 80^\circ\text{C}$	449	A	
$I_{Cnom}$			450	A	
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$		900	A	
$V_{GES}$			-20 ... 20	V	
$t_{psc}$	$V_{CC} = 600\text{ V}$ $V_{GE} \leq 20\text{ V}$ $V_{CES} \leq 1200\text{ V}$	$T_j = 125^\circ\text{C}$	10		$\mu\text{s}$
$T_j$			-40 ... 150	$^\circ\text{C}$	
<b>Inverse diode</b>					
$I_F$	$T_j = 150^\circ\text{C}$	$T_c = 25^\circ\text{C}$	561	A	
		$T_c = 80^\circ\text{C}$	384	A	
$I_{Fnom}$			450	A	
$I_{FRM}$	$I_{FRM} = 2 \times I_{Fnom}$		900	A	
$I_{FSM}$	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$		2900	A	
$T_j$			-40 ... 150	$^\circ\text{C}$	
<b>Module</b>					
$I_{t(RMS)}$			600	A	
$T_{stg}$			-40 ... 125	$^\circ\text{C}$	
$V_{isol}$	AC sinus 50Hz, t = 1 min		4000	V	

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>IGBT</b>						
$V_{CE(sat)}$	$I_C = 450\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	1.7	2.1		V
		$T_j = 125^\circ\text{C}$	2	2.45		V
$V_{CE0}$						
	$T_j = 25^\circ\text{C}$		1	1.2		V
	$T_j = 125^\circ\text{C}$		0.9	1.1		V
$r_{CE}$	$V_{GE} = 15\text{ V}$	$T_j = 25^\circ\text{C}$	1.6	2.0		$\text{m}\Omega$
		$T_j = 125^\circ\text{C}$	2.4	3.0		$\text{m}\Omega$
$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C = 18\text{ mA}$		5	5.8	6.5	V
$I_{CES}$	$V_{GE} = 0\text{ V}$ $V_{CE} = 1200\text{ V}$	$T_j = 25^\circ\text{C}$	0.1	0.3		$\text{mA}$
		$T_j = 125^\circ\text{C}$				$\text{mA}$
$C_{ies}$				32.3		nF
$C_{oes}$	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$			1.69	nF
$C_{res}$		$f = 1\text{ MHz}$			1.46	nF
$Q_G$	$V_{GE} = -8\text{ V...} + 15\text{ V}$				3600	nC
$R_{Gint}$	$T_j = 25^\circ\text{C}$				1.67	$\Omega$
$t_{d(on)}$	$V_{CC} = 600\text{ V}$ $I_C = 450\text{ A}$	$T_j = 125^\circ\text{C}$			310	ns
$t_r$		$T_j = 125^\circ\text{C}$			60	ns
$E_{on}$	$R_{Gon} = 1.6\ \Omega$				32	mJ
$t_{d(off)}$	$R_{Goff} = 1.6\ \Omega$				680	ns
$t_f$					135	ns
$E_{off}$					68	mJ
$R_{th(j-c)}$	per IGBT				0.061	K/W


**SEMiX® 33c**

## Trench IGBT Modules

### SEMiX703GD126HDc

#### Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$  with positive temperature coefficient
- High short circuit capability
- UL recognised file no. E63532


#### Typical Applications\*

- AC inverter drives
- UPS
- Electronic Welding

#### Remarks

- Case temperatur limited to  $T_C=125^\circ\text{C}$  max.
- Not for new design

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>Inverse diode</b>						
$V_F = V_{EC}$	$I_F = 450\text{ A}$ $V_{GE} = 0\text{ V}$ chip	$T_j = 25^\circ\text{C}$		1.6	1.80	V
		$T_j = 125^\circ\text{C}$		1.6	1.8	V
$V_{F0}$		$T_j = 25^\circ\text{C}$	0.9	1	1.1	V
		$T_j = 125^\circ\text{C}$	0.7	0.8	0.9	V
$r_F$		$T_j = 25^\circ\text{C}$	1.1	1.3	1.6	m $\Omega$
		$T_j = 125^\circ\text{C}$	1.6	1.8	2.0	m $\Omega$
$I_{RRM}$	$I_F = 450\text{ A}$	$T_j = 125^\circ\text{C}$		580		A
$Q_{rr}$	$di/dt_{off} = 8500\text{ A}/\mu\text{s}$	$T_j = 125^\circ\text{C}$		130		$\mu\text{C}$
$E_{rr}$	$V_{GE} = -15\text{ V}$ $V_{CC} = 600\text{ V}$	$T_j = 125^\circ\text{C}$		60		mJ
$R_{th(j-c)}$	per diode				0.11	K/W
<b>Module</b>						
$L_{CE}$				20		nH
$R_{CC'+EE'}$	res., terminal-chip	$T_C = 25^\circ\text{C}$		0.7		m $\Omega$
		$T_C = 125^\circ\text{C}$		1		m $\Omega$
$R_{th(c-s)}$	per module			0.014		K/W
$M_s$	to heat sink (M5)		3		5	Nm
$M_t$		to terminals (M6)	2.5		5	Nm
						Nm
$w$					900	g
<b>Temperatur Sensor</b>						
$R_{100}$	$T_C=100^\circ\text{C}$ ( $R_{25}=5\text{ k}\Omega$ )			$493 \pm 5\%$		$\Omega$
$B_{100/125}$	$R_{(T)}=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$ ; $T[\text{K}]$ ;			$3550$ $\pm 2\%$		K


**GD**




Fig. 1: Typ. output characteristic, inclusive  $R_{CC'+EE}$




Fig. 2: Rated current vs. temperature  $I_c = f(T_c)$




Fig. 3: Typ. turn-on /-off energy =  $f(I_c)$




Fig. 4: Typ. turn-on /-off energy =  $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs.  $I_C$




Fig. 8: Typ. switching times vs. gate resistor  $R_G$




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl.  $R_{CC+EE}$




Fig. 11: Typ. CAL diode peak reverse recovery current






Fig. 12: Typ. CAL diode recovery charge

Case: SEMiX 33c  
 general tolerance:  
 ISO 2768-mk  
 ISO 8015



SEMiX 33c



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

\* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.